Listing of the Claims:

This listing of claims will replace prior versions, and listings of claims in the application.

1.   (Previously Presented) A computer functioning as a computer-based network switch, comprising:

a first network adapter for connecting to an external network;

a plurality of second network adapters each for forming a connection with a network server in a private network;

a switching component for receiving network communication data from the external network through the first network adapter and directing the received network communication data to the second network adapters for transmission to the respective network servers in the private network connected thereto; and

a test control component for selectively disabling the second network adapters to create failure of physical connections between the second network adapters and the respective network servers in the private network connected thereto.

2.   (Previously presented) A computer as in claim 1, further including a third network adapter for connecting the test control component to the external network to allow the test control component to communicate with the external network.

3.   (Original)   A computer as in claim 1, wherein the switching

component is programmed to operate on network communication data passing

therethrough to create a communication test condition other than a connection failure

condition.

4.   (Original)   A computer as in claim 3, wherein the switching

component is programmed to delay network communication data passing therethrough.

5.   (Original)   A computer as in claim 3, wherein the switching

component is programmed to selectively drop network communication data.

6.   (Original)   A computer as in claim 3, wherein the switching

component is programmed to reorder data in a communication stream passing

therethrough.

7.   (Original)   A computer as in claim 3, wherein the switching

component is programmed to introduce errors into network communication data

passing therethrough.

8.   (Previously presented) A computer as in claim 1, wherein the switching component is programmed for monitoring flows of network communication data therethrough from the respective network servers in the private network to the external network.

9.   (Previously Presented) A computer-readable medium having computer-executable components for controlling a plurality of network adapters in a computer to create test conditions for testing network servers in a private network, the network servers connected to the network adapters, comprising:

a switching component for receiving network communication data from an external network and directing the received network communication data to the network adapters for transmission to the respective network servers in the private network connected thereto;

a test control for selectively disabling the network servers to create failure of physical connections between the network adapters and the respective network servers in the private network connected thereto.

10.   (Original)   A computer-readable medium as in claim 9, wherein the switching component includes further computer-executable instructions for operating

on network communication data passing therethrough to create a test condition other than a connection failure condition.

11.   (Original)   A computer-readable medium as in claim 10, wherein the switching component includes computer-executable instructions for selectively buffering network communication data passing therethrough for a delay period.

12.   (Original)   A computer-readable medium as in claim 10, wherein the switching component includes computer-executable instructions for selectively dropping network communication data passing therethrough.

13.   (Original)   A computer-readable medium as in claim 10, wherein the switching component includes computer-executable instructions for reordering data in a communication stream passing therethrough.

14.   (Original)   A computer-readable medium as in claim 10, wherein the switching component includes computer-executable instructions for introducing errors into network communication data passing therethrough.

15.   (Original)   A computer-readable medium as in claim 9, wherein the

test control includes computer-executable instructions for communicating with a server

testing controller to receive commands regarding testing of the network servers.

16.   (Original)   A computer-readable medium as in claim 9, wherein the

switching component includes further computer-executable instructions for monitoring

flows of network communication data from the respective network servers to the

external network.

17.   (Previously Presented) A system for testing network servers in a private

network, comprising:

a computer functioning as a computer-based network switch, including a

plurality of network adapters for forming connections to the network servers, a

switching component for receiving network communication data from an external

network and directing the received network communication data to the network

adapters for transmission to the respective network servers in the private network

connected thereto, and a test control for selectively disabling the network adapters;

a plurality of client computers connected to the external network for

communication with the network servers in the private network through the computer-

based network switch;

a server testing controller connected to the external network for coordinating

testing of the network servers, including instructing the client computers to send

network communication data to the network servers in the private network through the

computer-based network switch, and causing the test control to selectively disable the

network adapters to create failure of physical connections between the network adapters

and the network servers in the private network connected thereto.

18.   (Original)   A system as in claim 17, wherein the switching component

is controllable to operate on network communication data passing therethrough to

create a test condition other than a connection failure condition.

19.   (Original)   A system as in claim 18, wherein the switching component

is controllable to selectively buffer network communication data passing therethrough

to introduce a delay.

20.   (Original)   A system as in claim 18, wherein the switching component

is controllable to selectively drop network communication data passing therethrough.

21.   (Original)   A system as in claim 18, wherein the switching component

is controllable to reorder network communication data passing therethrough.

22.   (Original)   A system as in claim 18, wherein the switching component is controllable to introduce errors in network communication data passing therethrough.

23.   (Original)   A system as in claim 17, wherein the switching component is programmed for monitoring flows of network communication data from the network servers to the network clients.

24.   (Previously Presented) A method of testing a plurality of network servers in a private network, comprising the steps of:

connecting the network servers to a plurality of network adapters;

receiving network communication data from an external network;

directing the received network communication data to the network adapters for transmission to the respective network servers in the private network connected thereto;

selectively disabling the network adapters to create failure of physical connections between the network adapters and the network servers in the private network connected thereto.

25.   (Original)   A method as in claim 24, further including the step of operating on the network communication data received from the external network to

create a test condition other than a connection failure condition before sending the

network communication data to the network servers through the network adapters.

26.   (Original)   A method as in claim 25, wherein the step of operating

includes selectively buffering network communication data passing therethrough for a

delay period.

27.   (Original)   A method as in claim 25, wherein the step of operating

includes selectively dropping network communication data passing therethrough.

28.   (Original)   A method as in claim 25, wherein the step of operating

includes reordering network communication data passing therethrough.

29.   (Original)   A method as in claim 25, wherein the step of operating

includes introducing errors to network communication data passing therethrough.

30.   (Original)   A method as in claim 24, further including the step of

monitoring flows of network communication data from the network servers to the

external network..

31.   (Previously Presented) A computer comprising:

a first set of network adaptors configured to connect the computer to a plurality

of clients through a first network;

a second set of network adaptors configured to connect the computer to a

plurality of servers through a second network;

a switching module configured to identify incoming communication data from

the clients received by the first set of network adaptors and to send the communication

data to the servers through the second set of network adaptors; and

a testing module configured to create a failure of a physical connection to at

least one of the servers by disabling the network adaptor corresponding to the at least

one server in the second set of network adaptors;

wherein a fail-over mechanism associated with the plurality of servers is tested by the

failure of the physical connection created by the testing module.